HI-SPEED USB 2.0
2.5" EXTERNAL
ENCLOSURE
USER MANUAL
MODEL 702898

MANHATTAN™
BRINGING COMPUTERS TO LIFE

Congratulations on purchasing the MANHATTAN® Hi-Speed USB 2.0 2.5" External Enclosure, Model 702898. This device will let you quickly and easily transfer, share and archive data, and expand storage capacities for desktop and notebook PCs. Among the external enclosure's main features:

- Supports Hi-Speed USB 2.0 data transfer rates of up to 480 Mbps
- Lightweight, compact design requires no external power adapters for increased portability
- Sturdy aluminum case protects drive and facilitates cooling
- Fits standard 2.5" PATA (IDE) drives with easy, quick installation
- Windows and Macintosh compatible, Plug and Play, hot swappable
- Lifetime Warranty

SETTING UP THE EXTERNAL ENCLOSURE

NOTE: It's recommended that you first create a copy of your original data prior to connecting to the external enclosure to prevent the possibility of data loss should a mistake be made during the setup procedure. MANHATTAN accepts no responsibility for lost data.


1. Remove the back cover from the enclosure.

2. Carefully connect your drive to the interface.

3. Re-insert your drive into the enclosure.

4. Replace and tighten the two screws to complete the procedure.

USB 2.0 Windows 98SE Installation

1. Place the installation CD in the CD-ROM drive and connect the external enclosure to your computer. Auto Detect will run the Add New Hardware wizard, which searches for the USB 2.0 external enclosure. Click "Next."
2. Select "Search for the best driver for your device (recommended)" and then click "Next."
3. Click "Specify location"; browse to "CD-ROM E:\USB 2.0-98 Drive"; then click "Next."
4. With the prompt "Windows driver file search for the device Hi-Speed USB-to-IDE Bridge Controller," click "Next."
5. With the prompt "Windows has finished installing the software that your new hardware device requires," click "Finish."

NOTE: For Windows Me/2000/XP/Vista, no need to install the additional driver: It's already installed. Windows XP needs to be updated with SP2.

SPECIFICATIONS

- 44-pin IDE internal connection
- Hi-Speed USB 2.0 mini B external connection
- Prolific PL-2506 chipset
- DC power input jack (adapter not included)
- Meets current Hi-Speed USB 2.0 & IDE/ATA133 standards

- External DC power adapter cannot exceed 5 V / 1 A (not included)
- 14 x 8 x 1 cm (5.1 x 3.0 x 0.5 in.)
- 78 g (2.5 oz)

System Requirements
- Pentium 266 MHz or higher
- 64 MB RAM

- Windows 98SE/Me/2000/ XP/Vista or MAC OS 9.0 and above

Package Contents
- External Enclosure
- USB cable, A-type male x 2 to mini B male, 1.2 m (4 ft.)
- User manual and travel bag

MANHATTAN

MANHATTAN

BRINGING COMPUTERS TO LIFE

www.manhattan-products.com

Are you completely satisfied with this product?
Please contact your MANHATTAN® dealer with comments or questions.